

Professional Series - Infra Red

Infra Red High Speed PTZ System



New model
30x Zoom

Features:

- With infrared LED range up to 100 meters, it could capture image promptly at night
- Weatherproof design, high die-cast aluminum casing, protection grade IP66
- With wiper
- Super shockproof, especially suitable for car surveillance
- 360° continuously rotation, upward angle up to 180°
- 8 cruising tracks, each cruising track has 16 preset positions, 128 preset positions
- Input voltage: DC12V 5W-DC18V




Shock Absorber



Wall Bracket

Dimension



Specification

Model	108	128	168	278
Image sensor	1/4" CCD			
Active pixels	752(H) × 582(V)	752(H) × 582(V)	1280(H) × 960(V)	270(H) × 230(V)
Synchronization	Internal			
Video output	VBS-1 (25p/25 frame)			
White balance	Auto/Manual			
Scanning frequency	15.625KHz(H) 50Hz(V)			
Horizontal resolution	480TVL	480TVL	480TVL	480TVL
SNR ratio	50dB	≥ 50dB	50dB	≥ 50dB
Electronic shutter	1/3~1/10,000s	1/3~1/10,000s	1/3~1/10,000s	1/30~1/10,000s
Min. illumination	0 Lux (LED Open)			
Focal length	4.4~23.5mm 18 ×	4.5~40.5mm 23 ×	4.5~40.5mm 23 ×	4.5~40.5mm 23 ×
Focal & iris	Auto/Manual			
Pre preset speed	100°/s			
Tilt preset speed	60°/s			
Pre speed	2°~60°/s			
Tilt speed	2°~40°/s			
Pre range	360° Continuously			
Tilt range	+90° ~ -90°			
Preset, track	128 presets, 8 tracks			
Communication	Multi-protocol, Best rate from 2400bps to 18000bps for optional, RS485 control			
Relative humidity	90% without agglomeration			
IP grade	IP66			
Work temperature	-35℃ ~ 55℃			
Power supply	DC12V 5W-DC18V (2W VA)			
Shock	≥ 4G			
Weight	1kg			