

Professional Series

High Speed PTZ System



New model
36X Zoom
or more

Features

- High Die-cast Aluminum construction, high temperature proof, fire proof
- Weatherproof design, protection grade IP66
- 360° continuously
- Tilt range: +33° ~-63°
- 0.01 min. Illumination, Auto pan function between 2 presets
- 128 presets, 8 tracks
- Dust-proof, antifogging, frost protection function
- OSD English operate menu, 2 channels alarm-output

Dimension



Specification

Model	2016	2018	2021	2019	2022
Image sensor	1/4" CCD				
Active pixel	702(H) × 482(V)	702(H) × 482(V)	768(H) × 482(V)	702(H) × 482(V)	702(H) × 482(V)
Compression	MJPEG / H.264				
Video output	VBS 1.0Vp-p/75 ohm				
White balance	Auto/Manual				
Scanning frequency	15.625kHz/15.375kHz				
Horizontal resolution	480 TVL	480 TVL	480 TVL	480 TVL	480 TVL
Shutter	500	500	≥ 500	≥ 500	≥ 500
Electronic shutter	1/3~1/10,000s	1/3~1/10,000s	1/3~1/10,000s	1/3~1/10,000s	1/3~1/10,000s
Min. illumination	0.1 Lux	0.01 Lux	0.01 Lux	0.01 Lux	0.01 Lux
Pixel length	14.4~15.25mm (1)	14.4~15.25mm (1)	15.5~16.5mm (2)	15.5~16mm (2)	15.5~16mm (2)
Pixel & bit	Auto / Manual				
Pan preset speed	100% (s) (wind speed: 0m/10m/hour)				
Tilt preset speed	30% (s) (wind speed: 0m/10m/hour)				
Pan speed	0° ~360° /S				
Tilt speed	0° ~90° /S				
Pan range	360° continuously				
Tilt range	+33° ~-63°				
Preset track	128 presets, 8 tracks				
Control way	Multi protocol, Bus control from 2400bps to 10000bps, RS485 control				
Work temperature	-30°C ~ 55°C				
Relative humidity	90% without agglutination				
IP grade	IP66				
Power supply	AC 24VAC / 18V AC 230V				
Power consumption	7W/A				
Weight	10.8kg				