

## Professional Series

### Outdoor High Speed Dome Camera



New model  
30X Zoom

#### Features:

- High Die-cast Aluminum Construction
- Low noise design
- OSD function
- 128 preset positions
- 6 cruising tracks, each cruising track has 16 preset positions
- 6 privacy zone marking
- 48s Pattern Tours (path memory function)
- Multi-protocol communication
- RS485 data communication
- 4-Alarm input and 1-Alarm output
- AC24V input
- Built-in fan and heater

#### Optional Parts



Ceiling Bracket

Wall Bracket

Sunglasses Glass Dome Cover

#### Dimension



#### Specification

Model	180C	180E	215E	255E	275E
Image sensor	1/4" CCD				
Active pixel	752(H) × 582(V)	752(H) × 582(V)	752(H) × 582(V)	752(H) × 582(V)	752(H) × 582(V)
Synchronization	Internal Burster				
Video output	VBS 1.0Vp-p/75 ohms				
White balance	Auto Manual				
Scanning frequency	H:50/60Hz(V) 50Hz(V)				
Horizontal resolution	480 TVL	480 TVL	480 TVL	480 TVL	480 TVL
Shutter	500μs	500μs	μ:500μs	μ:500μs	μ:500μs
Electronic shutter	1/2~1/10,000s	1/2~1/10,000s	1/2~1/10,000s	1/2~1/10,000s	1/2~1/10,000s
Min. Illumination	0.7Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux
Focal length	F4.1-13.8mm 18°	F4.1-70.5mm 18°	F4.1-82.8mm 25°	F4.5-100mm 25°	F4.5-88mm 27°
Focal & iris	Auto/Manual				
Pan speed	0°~360°/s				
Tilt speed	0°~130°/s				
Pan range	360° Continuously				
Tilt range	90° (180° auto overflow)				
Power	1/2(max)				
Communication	Multi-protocol, RS485				
Relative humidity	90% without agglutination				
Work temperature	-30°C~55°C				
Power supply	AC 24V				
Power consumption	20VA				
Weight	40g				